

03A

Specifications for IndentNo :25BPIC201

Dated : 11 Feb 2025

IndLNo Item Code

Item Description

1 EP3004V-PAN7400

HEADSET CONNECTION BOX

IndLNo Item Code

Item Description

2 EP3030B-0007988

16X0.2MM, 2 CORE SHIELDED UN-ARMoured MICROPHONE CABLE

IndLNo Item Code

Item Description

3 EP3030B-0013075

1 PAIR CABLE, CONDUCTOR MULTI-STRAND ATC SIZE 24/0.2MM

Specification :

DEF STAN : 61-12 PT.18/5
DEF STAN : 61-12 PT.31/2
IS:8130 : 2013

Characteristic :

CLASS OF CONDUCTOR : V
CONDUCTOR DIAMETER : 1.14 mm
CORE IDENTIFICATION : SINGLE PAIR
CROSS SECTION AREA : 0.75 Sq.mm
DIA. OVER SHEATH : 6.48 MM
DIAMETER OF PAIR : 4.68 mm
DIAMETER OF STRAND : 0.2 mm
FILLING OF CORE INTERSTICE : OPTIONAL
IDENTIFICATION OF SHEATH : Mfg. name, Size, Voltage, Year of Mfg.
INSULATION CORE DIAMETER : 2.34 mm
INSULATION MATERIAL : LFH
MATERIAL OF CONDUCTOR : ATC
MATERIAL OF SHEATH : LFH
MAX. DC RESIS. AT 20 DEG. C : 26.7 Ohms/Km
NO. OF PAIR : 1
NO. OF STRANDS : 24
OVERALL BRAIDING DIA. OF WIRE : 0.15 mm
OVERALL BRAIDING MATERIAL : ATC
OVERALL BRAIDING MIN. COVERAGE : 80%
OVERALL DIAMETER : 7.38 mm
RADIAL THICKNESS OF INSULATION : 0.6 mm
RADIAL THICKNESS OF SHEATH : 0.9 mm
TAPE LAID UP CORE DIAMETER : 4.68 mm
TAPE/FIBRE GLASS BRAID & LACQU : OPTIONAL
VOLTAGE : 440 V

Specifications for IndentNo :25BPIC201

Dated : 11 Feb 2025

IndLNo Item Code

37 EP3030B-0013118

Item Description

4 CORE CABLE, CONDUCTOR MULTI-STRAND ATC SIZE
24/0.2MM

Specification :

DEF.STAN : 61-12 PT.18/5

DEF.STAN : 61-12 PT.31/2

IS:8130 : 2013

Characteristic :

CLASS OF CONDUCTOR : V

CONDUCTOR DIAMETER : 1.14 mm

CORE DIAMETER : 2.34 mm

CORE IDENTIFICATION : By Numbering

CROSS SECTION OF AREA : 0.75 Sq.mm

DIA. OVER SHEATH : 7.46 mm

DIAMETER OF STRANDS : 0.2 mm

FILLING OF CORE INTERSTICE : Optional

IDENTIFICATION OF SHEATH : Mfg. Name, Size, Voltage, Year of Mfg.

MATERIAL OF CONDUCTOR : ATC

MATERIAL OF INSULATION : LFH

MATERIAL OF SHEATH : LFH

MAX.DC RESIS. AT 20 DEG. C : 26.7 Ohms/Km

NO. OF PAIRS : 4

NO. OF STRANDS : 24

OVERALL BRAIDING DIA. OF WIRE : 0.15 mm

OVERALL BRAIDING MATERIAL : ATC

OVERALL BRAIDING MIN. COVERAGE : 80%

OVERALL DIAMETER : 8.36 mm

RADIAL THICKNESS OF INSULATION : 0.6 mm

RADIAL THICKNESS OF SHEATH : 0.9 mm

SCREENING : SCREENING REQUIRED OVER THE SHEATH

TAPE LAID UP CORE DIAMETER : 5.66 mm

TAPE/FIBRE GLASS BRAID&LACQUER : Optional

VOLTAGE : 440 V

IndLNo Item Code

32 EP3030B-1100270

Item Description

ZONE INTERFACE CARD

IndLNo Item Code

43 EP3030B-1100480

Item Description

POWER SUPPLY CARD

IndLNo Item Code

38 EP3030B-1100760

Item Description

CPU CARD

IndLNo Item Code

30 EP3030B-1100850

Item Description

LOOP CARD

IndLNo Item Code

44 EP3030B-1392UPS

Item Description

UPS WITH BATTERIES-1 HOUR BACKUP

IndLNo Item Code

31 EP3030B-2014160

Item Description

20 PAIR 0.5 MM DIA ATC SOLID CONDUCTOR LFH SHEATHED CABLE

IndLNo Item Code

39 EP3030B-2018911

Item Description

2 CORE, CONDUCTOR 7/0.67 L.E 2.5SQ.MM, LFH SHEATHED

Specification :

DEF. STAN : 61-12 PT.18/5

DEF. STAN : 61-12 PT.31/2

IS:8130 : 2013

Characteristic :

CONDUCTOR DIAMETER : 2.01 mm

CORE DIAMETER : 3.81 mm

CORE IDENTIFICATION : By Numbering

CROSS SECTION AREA : 2.5 Sq.mm

DIA. OVER SHEATH : 10.02 mm

DIAMETER OF STRANDS : 0.67 mm

FILLING OF CORE INTERSTICE : Optional

IDENTIFICATION OF SHEATH : Mfg. Name, Size, Voltage, Year of Mfg.

INSULATION MATERIAL : LFH

MATERIAL OF CONDUCTOR : ATC

MAX.DC RESIS. AT 20 DEG.C : 7.56 Ohms/Km

NO. OF CORES : 2

NO. OF STRANDS : 7

OVERALL BRAIDING DIA OF WIRE : 0.15 mm

OVERALL BRAIDING MATERIAL : ATC

OVERALL BRAIDING MIN COVERAGE : 80%

OVERALL DIAMETER : 10.92 mm

RADIAL THICKNESS OF INSULATION : 0.9 mm

RADIAL THICKNESS OF SHEATH : 1.2 mm

SCREENING : SCREENING REQUIRED OVER THT SHEATH

SHEATH MATERIAL : LFH

TAPE/FIBRE GLASS BRAID&LACQUER : Optional

TAPED LAID UP CORE DIAMETER : 7.52 mm

VOLTAGE : 440 V

IndLNo Item Code

4 EP3030B-2423512

Item Description

SPEAKER

Specification :

WNC APPR. DRG. : M & S 308

IndLNo Item Code

33 EP3030B-768-ICOM-INST

Item Description

INSTALLATION ACCESSORIES FOR ICOM

IndLNo Item Code

40 EP3030B-DOCS-1076I-COM

Item Description

DOCUMENTATION

IndLNo Item Code

42 EP3030B-DOCS-1076MB

Item Description

DOCUMENTATION

Specifications for IndentNo :25BPIC201

Dated : 11 Feb 2025

IndLNo Item Code

5 EP3030B-FOOTSWITCH

Item Description

FOOT SWITCH FOR GOOSENECK MICROPHONE

IndLNo Item Code

14 EP3030B-INST-921

Item Description

INSTALLATION ACCESSORIES

IndLNo Item Code

41 EP3030B-KEYBOARD

Item Description

KEYBOARD

IndLNo Item Code

15 EP3030B-LBD8308M

Item Description

DRIVER UNIT

Specification :

WNC APPR. DRG. : M & S 308

IndLNo Item Code

8 EP3030B-PAN1414-00+PAN6702

Item Description

SPLASHPROOF MIC WITH STOWAGE CLAMP & 7 PIN PLUG(INTERPHONE)

IndLNo Item Code

9 EP3030B-PAN1424-00+PAN6702

Item Description

SPLASHPROOF MIC+STOWAGE HOOK PREAMP&7PIN PLUG-MBSRE/INTERCOM

Characteristic :

PIN PLUG : 7 PIN

IndLNo Item Code

10 EP3030B-PAN1510-01

Item Description

MICROPHONE STOWAGE BOX

Specification :

WNC APPR. DRG. : M & S 308

IndLNo Item Code

11 EP3030B-PAN1510-1392

Item Description

ANNOUNCEMENT POINT STOWAGE BOX

IndLNo Item Code

12 EP3030B-PAN2501-01

Item Description

3-POLE 3-WAY JUNCTION BOX

IndLNo Item Code

13 EP3030B-PAN2507

Item Description

JUNCTION Box L4 Type

IndLNo Item Code

6 EP3030B-PAN2508

Item Description

JUNCTION BOX L5 Type

IndLNo Item Code

34 EP3030B-PAN5713

Item Description

240W POWER AMPLIFIER

IndLNo Item Code

7 EP3030B-PAN5967-662

Item Description

I/O COMBINED RACK VARIOUS SUBRACKS& MUSIC SOURCES-DVD PLAYER

IndLNo Item Code

16 EP3030B-PAN5969-1319

Item Description

COMBINED INTERCOM RACK

IndLNo Item Code

17 EP3030B-PAN6402-01

Item Description

MICROPHONE CONNECTION BOX

IndLNo Item Code

18 EP3030B-PAN6702

Item Description

PLUG (7 PIN)

IndLNo Item Code

19 EP3030B-PAN8533

Item Description

OUTDOOR COMMUNICATION STATION

IndLNo Item Code

20 EP3030B-PAN9614

Item Description

LOUDSPEAKER 1/2/4W(NWT)

IndLNo Item Code

21 EP3030B-PAN9621-PAN7409-A

Item Description

HORN LS(15W) SET AT 8W

IndLNo Item Code

22 EP3030B-PAS00600

Item Description

PCB ASSEMBLY MAIN 240W

IndLNo Item Code

23 EP3030B-PAS00620

Item Description

PCB ASSEMBLY MAIN 120W AMPLIFIER

IndLNo Item Code

24 EP3030B-PAS1269-90

Item Description

24VDC POWER SUPPLY

Specifications for IndentNo :25BPIC201

Dated : 11 Feb 2025

IndLNo **Item Code**
25 EP3030B-PAS30240

Item Description
LINE INTERFACE CARD

IndLNo **Item Code**
26 EP3030B-PAS3198

Item Description
MICROPHONE WITH FLEXIBLE GO

IndLNo **Item Code**
27 EP3030B-PAS41590

Item Description
PREAMPLIFIER FOR PAN 1424-00

IndLNo **Item Code**
35 EP3030B-PAS62290

Item Description
PCB ASSEMBLY FOR RELAY PANEL

IndLNo **Item Code**
36 EP3030B-PCB-SET-8533

Item Description
PCB ASSEMBLY SET FOR PAN8533

IndLNo **Item Code**
28 EP3030B-Q34-02NM-1318

Item Description
HEADSET WITH 7 POLE CONNECTOR & PRE-AMP

IndLNo **Item Code**
29 EP3030B-UPS-1319

Item Description
UPS WITH BATTERIES FOR 1 HOUR BACK UP
