

To, M/s. BPCL ESTIMATE MUMBAI . India - 400038. Ph: ,Fax: . <b>Vendor Code:300648</b>	<b>REQUEST FOR QUOTATION</b> <b>Collective RFQ Number/ Purchase Group</b> 1000455674 / J03-IMPORT & ELECTRICL <b>Contact person/Telephone</b> BIJU K A/. <b>Fax :</b> <b>Email:bijuka@bharatpetroleum.in</b> <b>Our ref.: 2263006</b>			
<b>RFQ No/Date:</b> 6001932287 / 28.04.2026	<b>Quotation Due Date/Time:</b> 19.05.2026/15:00:00			
<b>Material/Services required at:</b> M/s.  KOCHI ERNAKULAM- 682302 India				
<b>Subject: CABLE POWER &amp; CONTROL TPE</b> Kind Attn:  Please quote your lowest prices for the supply of materials/services as per details given below. The quotation shall show separately and clearly (without any corrections) the basic price, discount (%), packing & forwarding (%), GST, freight(%), other charges, etc against each item separately, as applicable. <b>Foreign vendors shall always quote their FOB prices against each item.</b> Rates/charges quoted in the quotation shall be final and no additional charges/corrections will be accepted after the receipt of quotation unless the same is necessitated by BPCL in writing.				
<b>Item</b>	<b>Material Description</b>	<b>Qty</b>	<b>Unit Delivery date</b>	<b>Unit Basic Rate (in Figures)</b>
00010	68.23.61.997.5 <b>CABLE POWER TPE 1KV 4CX25 SQMM</b>  SHORT DESCRIPTION : CABLE POWER TPE 1KV 4CX25 SQMM MATGRP : 68 UOM : M ITEM DESCRIPTION : FLEXIBLE POWER CABLE, 4 CORES x 25 SQMM APPLICATION : POWER CABLE FOR CONTINUOUS FLEXING APPLICATIONS IN ENERGY CHAINS® AND APPLICATIONS IN ENERGY CHAINS® AND DYNAMIC INSTALLATIONS. VOLTAGE RATING : 600/1000 V (AS PER DIN VDE 0250). TESTING VOLTAGE : 4000 V (AS PER DIN VDE 0281-2). CONDUCTOR: < 10 MM <sup>2</sup> : FINE STRANDED COPPER CONDUCTORS, HIGH BENDING RESISTANCE (AS PER EN 60228). = 10 MM <sup>2</sup> : CONDUCTOR MADE OF PRE-STRANDED LEADS (AS PER EN 60228). CORE INSULATION: LOW-CAPACITANCE, MECHANICALLY ROBUST TPE COMPOUND. CORE IDENTIFICATION: BLACK CORES WITH WHITE NUMERALS, ONE GREEN-YELLOW PROTECTIVE CONDUCTOR. PHASE/CORE MARKING: U / L1 / C / L+ V / L2 W / L3 / D / L# N / 4 CORE STRANDING: SHORT PITCH STRANDING OVER A CENTRAL ELEMENT FOR HIGH TENSILE STRESS ABSORPTION. OUTER SHEATH: PUR/TPE OUTER SHEATH WITH UL/CSA APPROVAL WITH	300.000	m 22.10.2026	
Page 1 of 6	Vendor Sign & Stamp		For Bharat Petroleum Corporation Ltd.	

RFQ Number :6001932287

Date : 28.04.2026

To:M/s. BPCL ESTIMATE MUMBAI - 400038 India (300648)

Item	Material Description	Qty	Unit	Delivery date	Unit Basic Rate (in Figures)
	AN OPERATING VOLTAGE OF 0.6/1 KV. COLOUR: BLACK (APPROX. RAL 9005). TEMPERATURE RANGE: FIXED INSTALLATION: #40 °C TO +90 °C, MIN. BENDING RADIUS 4 × D. MOVING INSTALLATION: #35 °C TO +90 °C, MIN. BENDING RADIUS 7.5 × D. DYNAMIC PERFORMANCE: MAX. ACCELERATION: 80 M/S <sup>2</sup> . MAX. TRAVEL SPEED: 10 M/S (UNSUPPORTED), 6 M/S (GLIDING). TRAVEL DISTANCE: UP TO 400 M AND ABOVE, CLASS 4. RESISTANCE PROPERTIES: UV-RESISTANT: HIGH. OIL-RESISTANT (DIN EN 60811-2-1). BIO-OIL-RESISTANT (VDMA 24568), CLASS 4. SILICON-FREE (PV 3.10.7 # 1992). HALOGEN-FREE (EN 50267-2-1)				
State GST % : _____ %    Central GST % : _____ %    Integrated GST % : _____ %					
Union Ter. GST % : _____ %    GST Comp. Cess % : _____ %					
HSN Code / SAC Code : _____					
Billing State : _____					
Packing & Forwarding Charges : _____ % per unit OR _____ (INR) per unit					
Freight Charges : _____ % per unit OR _____ (INR) per unit					
Third party Inspection charges : _____ % per unit OR _____ (INR) per unit					
Other charges (if any ) : Please specify separately					
00020	68.23.61.998.5 CABLE POWER TPE 1KV 4CX4 SQMM	300.000	m	22.10.2026	
	SHORT DESCRIPTION : CABLE POWER TPE 1KV 4CX4 SQMM MATGRP : 68 UOM : M ITEM DESCRIPTION : FLEXIBLE POWER CABLE, 4 CORES×4 SQMM APPLICATION : POWER CABLE FOR CONTINUOUS FLEXING APPLICATIONS IN ENERGY CHAINS® AND DYNAMIC INSTALLATIONS. VOLTAGE RATING : 600/1000 V (AS PER DIN VDE 0250). TESTING VOLTAGE : 4000 V (AS PER DIN VDE 0281-2). CONDUCTOR: < 10 MM <sup>2</sup> : FINE STRANDED COPPER CONDUCTORS, HIGH BENDING RESISTANCE (AS PER EN 60228). = 10 MM <sup>2</sup> : CONDUCTOR MADE OF PRE-STRANDED LEADS (AS PER EN 60228). CORE INSULATION: LOW-CAPACITANCE, MECHANICALLY ROBUST TPE COMPOUND. CORE IDENTIFICATION: BLACK CORES WITH WHITE NUMERALS,				
Page 2 of 6		Vendor Sign & Stamp		For Bharat Petroleum Corporation Ltd.	

RFQ Number :6001932287

Date : 28.04.2026

To:M/s. BPCL ESTIMATE MUMBAI - 400038 India (300648)

Item	Material Description	Qty	Unit Delivery date	Unit Basic Rate (in Figures)
	<p>ONE GREEN-YELLOW PROTECTIVE CONDUCTOR.            PHASE/CORE MARKING: U / L1 / C / L+ V / L2 W / L3 / D / L# N / 4            CORE STRANDING: SHORT PITCH STRANDING OVER A CENTRAL ELEMENT FOR HIGH TENSILE STRESS ABSORPTION.            OUTER SHEATH: PUR/TPE OUTER SHEATH WITH UL/CSA APPROVAL WITH AN OPERATING VOLTAGE OF 0.6/1 KV.            COLOUR: BLACK (APPROX. RAL 9005).            TEMPERATURE RANGE: FIXED INSTALLATION: #40 °C TO +90 °C, MIN. BENDING RADIUS 4 × D.            MOVING INSTALLATION: #35 °C TO +90 °C, MIN. BENDING RADIUS 7.5 × D.            DYNAMIC PERFORMANCE: MAX. ACCELERATION: 80 M/S<sup>2</sup>.            MAX. TRAVEL SPEED: 10 M/S (UNSUPPORTED), 6 M/S (GLIDING).            TRAVEL DISTANCE: UP TO 400 M AND ABOVE, CLASS 4.            RESISTANCE PROPERTIES: UV-RESISTANT: HIGH.            OIL-RESISTANT (DIN EN 60811-2-1).            BIO-OIL-RESISTANT (VDMA 24568), CLASS 4.            SILICON-FREE (PV 3.10.7 # 1992).            HALOGEN-FREE (EN 50267-2-1)</p>			
<p>State GST % : _____ %    Central GST % : _____ %    Integrated GST % : _____ %</p> <p>Union Ter. GST % : _____ %    GST Comp. Cess % : _____ %</p> <p>HSN Code / SAC Code : _____</p> <p>Billing State : _____</p> <p>Packing &amp; Forwarding Charges : _____ % per unit OR _____ (INR) per unit</p> <p>Freight Charges : _____ % per unit OR _____ (INR) per unit</p> <p>Third party Inspection charges : _____ % per unit OR _____ (INR) per unit</p> <p>Other charges (if any ) : Please specify separately</p>				
00030	68.23.61.999.5	600.000	m	
	CABLE CNTRL TPE 300V 4P 2CX1.0 SQMM		22.10.2026	
	SHORT DESCRIPTION	: CABLE CNTRL TPE 300V 4P 2CX1.0 SQMM		
	MATGRP	: 68		
	UOM	: M		
	ITEM DESCRIPTION	: FLEXIBLE DATA AND SIGNAL CABLE, 4 PAIRS × 2 CORES × 1.0 SQMM		
	APPLICATION	: SHIELDED DATA/CONTROL CABLE FOR CONTINUOUS FLEXING APPLICATIONS IN ENERGY CHAINS® AND		
Page 3 of 6		Vendor Sign & Stamp		For Bharat Petroleum Corporation Ltd.

RFQ Number :6001932287

Date : 28.04.2026

To:M/s. BPCL ESTIMATE MUMBAI - 400038 India (300648)

Item	Material Description	Qty	Unit Delivery date	Unit Basic Rate (in Figures)
	DYNAMIC INSTALLATIONS. VOLTAGE RATING : 300/300 V (AS PER DIN VDE 0245). TESTING VOLTAGE : 1500 V. CONDUCTOR : FINE-WIRE, STRANDED BARE COPPER CONDUCTORS, HIGH BENDING RESISTANCE (AS PER EN 60228). CORE INSULATION : MECHANICALLY ROBUST TPE COMPOUND. CORE STRANDING: PAIRS STRANDED WITH SHORT PITCH LENGTHS. MULTIPLE PAIRS STRANDED TOGETHER WITH SHORT PITCH LENGTHS FOR HIGH FLEXIBILITY. CORE IDENTIFICATION:< 1.0 MM <sup>2</sup> : COLOUR CODE AS PER DIN 47100. = 1.0 MM <sup>2</sup> : BLACK CORES WITH WHITE NUMERALS. INNER JACKET: TPE MIXTURE, DESIGNED FOR HIGH FLEXIBILITY IN ENERGY CHAIN APPLICATIONS. SHIELDING:TINNED COPPER BRAID, EXTRA FLEXIBLE. COVERAGE APPROX. 70% LINEAR, ~90% OPTICAL. OUTER SHEATH: PUR/TPE OUTER SHEATH WITH UL/CSA APPROVAL WITH AN OPERATING VOLTAGE OF 0.6/1 KV. COLOUR: DARK BLUE (APPROX. RAL 5011). TEMPERATURE RANGE: FIXED INSTALLATION: #40 °C TO +100 °C, MIN. BENDING RADIUS 5 × D. MOVING INSTALLATION: #35 °C TO +100 °C, MIN. BENDING RADIUS 10 × D. DYNAMIC PERFORMANCE: MAX. ACCELERATION: 100 M/S <sup>2</sup> . MAX. TRAVEL SPEED: 10 M/S (UNSUPPORTED), 6 M/S (GLIDING). TRAVEL DISTANCE: UP TO 400 M AND ABOVE, CLASS 4. RESISTANCE PROPERTIES: UV-RESISTANT: HIGH. OIL-RESISTANT (DIN EN 60811-2-1). BIO-OIL-RESISTANT (VDMA 24568), CLASS 4. SILICON-FREE (PV 3.10.7 # 1992). HALOGEN-FREE (EN 50267-2-1). LEAD-FREE (ROHS 2002/95/EC COMPLIANT). COMPLIANCE: CE MARKING AS PER 2006/95/EG			
State GST % : _____ %    Central GST % : _____ %    Integrated GST % : _____ % Union Ter. GST % : _____ %    GST Comp. Cess % : _____ % HSN Code / SAC Code : _____ Billing State : _____ Packing & Forwarding Charges : _____ % per unit OR _____ (INR) per unit Freight Charges : _____ % per unit OR _____ (INR) per unit				
Page 4 of 6		Vendor Sign & Stamp		For Bharat Petroleum Corporation Ltd.

To:M/s. BPCL ESTIMATE MUMBAI - 400038 India (300648)

Item	Material Description	Qty	Unit Delivery date	Unit Basic Rate (in Figures)
Third party Inspection charges : _____ % per unit OR _____ (INR) per unit				
Other charges (if any ) : Please specify separately				

**1. Other contractual stipulations**

OFFER SHALL BE UPLOADED IN GeM PORTAL.

PRICE QUOTED SHALL BE INCLUSIVE OF P&F, FREIGHT AND GST.

DELIVERY PERIOD: 3 MONTHS FROM THE DATE OF PURCHASE ORDER.

MATERIAL SHALL BE SUPPLIED AT BPCL-KOCHI REFINERY, AMBALAMUGAL, ERNAKULAM DIST, KERALA - 682302 ON FREIGHT PAID DOOR DELIVERY BASIS.

OFFER SHALL BE UPLOADED IN GeM PORTAL ALONG WITH DETAILED TECHNICAL SPECIFICATIONS, DATA SHEETS, BQC DOCUMENTS AND SIGNED ATC WITH SEAL.

TENDER CONDITIONS SHALL BE AS PER ATC ATTACHED IN GeM PORTAL WHICH SHALL BE FILLED WITH SIGN AND SEAL AND UPLOADED ALONG WITH TENDER DOCUMENTS.

**Important Notice**

Sr.No	Description
001	Quotation received after due date will not be entertained
002	Your quotation must specify exact amount or percentage discount, GST, Charges, Transport, Packing & forwarding, etc. as applicable.
003	In case you are unable to quote, kindly send the quotation with a regret for our records. Non-receipt of a regret will adversely affect your vendor rating.
004	No quotation will be accepted without your rubber stamp and signature.
005	Your quotation must be strictly in enclosed envelope indicating Collective RFQ No., RFQ No. and due date.
006	For all future correspondences please mention the vendor code Collective RFQ Number & RFQ Number.

To:M/s. BPCL ESTIMATE MUMBAI - 400038 India (300648)

-----Tear off Portion to be pasted on the envelope containing offer-----

**Collective RFQ No. : 1000455674**

Our Reference: 2263006

Due Date : 19.05.2026

RFQ No. : 6001932287

Due Time : 15:00:00

Subject: CABLE POWER & CONTROL TPE

To,  
MANAGER (P&CS)  
BPCL - KOCHI REFINERY  
POST BAG NO 2, AMBALAMUGAL  
KOCHI, INDIA  
682302

Purchase Group : J03-IMPORT & ELECTRICL