

Sl. no.	Model name	Technical Specifications	Qty	Unit
1	Computer table	SUPPLYING AND PLACING IN POSITION OF COMPUTER TABLE Size :935mm X480mm X 750mm) Durable Materials: 18mm thick Pre-Laminated Particle Board for top and Gable End. Functional Design: Modesty crafted from 18mm thick Particle Board. Enhanced Stability: Gable foot brackets made of steel with nylon levelers. Organized Storage: 3 drawers with central locking mechanism. Structural Integrity: Reinforcement tube prevents sagging. Standard Finishes: Graphite Grey, Thansu Maple, Walnut, Wenge.	1	NO's
2	Visitor Sofa 1Seater	SUPPLYING AND PLACING IN POSITION OF 1 SEATER MODERNIST CLASSIC DESIGN SOFA Overall Dimensions for 1seater _ 740mm (L) X710mm (D)X 820mm (H) & Weight-9kg MATERIAL : Primary MaterialPlastic - Polypropylene Color - Brown * Premium plastic for exceptional durability, ensuring it withstands daily wear and tear. * Soft, fabric-covered cushions offer cosy and comfortable seating, perfect for extended lounging sessions. * Sturdy design supports up to 125 kg per seat, providing reliable strength and stability. * UV-treated material ensures suitability for outdoor use, protecting against sun damage and fading. * Perfect for enhancing the aesthetic and comfort of homes, gardens, hotels, and resorts, adding a touch of elegance. THE SELLER/ OEM SHOULD BE NABCB CERTIFIED ISO9001:2015; ISO14001:2015; ISO45001:2018; ISO50001:2018. UL-GREENGUARD GOLD , GRIHA, CII Certified Green Co Gold Certificate, CII Certified GREENPRO, AIOTA, CERTIFIED, Indian design mark certificate for one or more products. THE BIDDER SHOULD ALSO BE A MEMBER OF BIFMA AND ONE OR MORE PRODUCTS OF THE OEM SHOULD BE CERTIFIED AS BIFMA COMPLIANT AND AN OFFICIAL PRODUCT LINK/SCREENSHOT OF THE PRODUCT LISTING'S MUST BE PROVIDED FROM WWW.BIFMA.ORG" IN EACH CASE.	4	NO's
3	Steel Almirah	Supplying and placing in position of Steel Almirah (Magna) - Steel Almirah plain shall have an overall size of 900mm(W)x450mm(D) x1981mm(H) with welded construction. It should have the shelf thickness of 0.7 mm, Back thickness of 0.8mm, Door thickness of 0.8mm (high yield strength) and all other components shall have a thickness of 0.9mm. These components shall be made of CRCA 'D' grade high yield strength as per IS:513. The Storvel Plain should have a Mazak handle and Three way locking mechanism with Shooting Bolts. It should have a height wise adjustable shelf mounting which shall have a Uniformly Distributed Load Capacity of max 40 Kg. It should also have a M10 Screw type Leveller with Hex plastic base. The finishing shall include Epoxy powder coated to the thickness of 50 microns (+/- 10).	2	NO's
4	Work Table / Computer Table	Supply, assembly and placement of Table of following specifications: Size shall be 1500 Width mm x 750 Depth mm x 750 Height mm.The table top shall be made of pre- laminated particle board with 18 mm thick and 15 mm thick understructure covered with PVC lipping .There shall be locking provided for top drawers only (as per the product image), etc., all complete as per directions of the Engineer-in-charge. THE SELLER/ OEM SHOULD BE NABCB CERTIFIED ISO9001:2015; ISO14001:2015; ISO45001:2018; ISO50001:2018. UL-GREENGUARD GOLD , GRIHA, CII Certified Green Co Gold Certificate, CII Certified GREENPRO, AIOTA, CERTIFIED, Indian Design Mark certificate for one or more products. THE BIDDER SHOULD ALSO BE A MEMBER OF BIFMA AND ONE OR MORE PRODUCTS OF THE OEM SHOULD BE CERTIFIED AS BIFMA COMPLIANT AND AN OFFICIAL PRODUCT LINK/SCREENSHOT OF THE PRODUCT LISTING'S MUST BE PROVIDED FROM WWW.BIFMA.ORG" IN EACH CASE.	1	NO's
5	Mid back Revolving Chair	Providing, supplying and placing of Victory Mid Back Chair with following specifications: SEAT/BACK ASSEMBLY: The seat is made up of 12mm thk. hot pressed plywood measured.The Back is made up of injection moulded glass filled nylon & upholstered with high quality fabric. *HIGH RESILIENCE (HR) POLYURETHANE FOAM: The HR polyurethane seat foam is moulded with density 45+/-2 kg/m³ and hardness 16 ± 2 kgf as per IS:7888 for 25% compression. ARMRESTS : The adjustable armrest is designed with the following features : •Up-Down adjustment •Height adjustable armrest structure which is Powder Coated & fitted with an armrest top. •Fixed Armrest Top is PU moulded over metal insert. LUMBAR SUPPORT ASSEMBLY: The Lumbar support consists of polypropylene pad with moulded polyurethane foam & covered with polyester fabric.The Height of Lumbar pad can be adjusted through two projecting knobs provided on the rear side of the pad. Overall dimension - 710 (W) x 700 (D) x 1170/1270 (H) mm Synchronic mechanism & PNEUMATIC HEIGHT ADJUSTMENT. The pneumatic height adjustment has an adjustment stroke of 10.0 ± 0.3 cm. Pedestal Assembly : the pedestal is injection moulded in black 30% glass filled nylon and fitted with 5 nos. twin wheel castors. The pedestal pitch center dia is 66.1± 0.5 cm. TWIN WHEEL CASTORS: The twin wheel castors are injection moulded in black Nylon. NECKREST : The Neckrest assembly consist of polypropylene pad with moulded polyurethane foam & covered with polyester fabric Neckrest is fixed to Back Assembly through Neckrest connector Neckrest assembly has height adjustment of 4.2 ± 0.5 cm and rotation adjustment of overall 76°+ 2°. The complete neckrest assembly is retro fit to the main chair., etc., all complete as per directions of the Engineer-in-charge.	1	NO's

6	Work Table / Computer Table	SUPPLYING AND PLACING IN POSITION OF OFFICE DESK DESK STRUCTURE OF RECTANGULAR SHAPE . PRIMARY WORK SURFACE OVER ALL SIZE IS 1200MM (LX 600MM (DX 750MM (H 25MM THICK TABLE TOP MADE OF PRELAMINATED PARTICLE BOARD WORK SURFACE WITH THE EXPOSED EDGES SHALL BE FINISHED WITH 2MM THICK EDGE BINDING TAPE OF MATCHING COLOUR AND SHADE WITH THE HOT MELT GLUE . MODESTY PANEL MADE OF MM THICK. UNDERSTRUCTURE MADE OF 18MM THICK WITH WIRE MANAGEMENT HOLE WITH PVC GROOMENT ON TABLE TOP. PROVISION OF SIDE UNIT OF SIZE IS 600MM (LX 400MM (DX 600MM (H ,(COMBINATION CONSTRUCTION FULL TABLE LOOK LIKE IN H-SHAPE FROM FRONT SIDE SIDE AND TABLE TOP IS BASED ON 2 + 2 80MM THICK BOXES SHAPE MADE IN SAME AS ENGINEERED WOOD TABLE IS MADE IN A DIFFERENT STYLE RIGHT SIDE FIXED PEDESTAL WITH 3 DRAWERS + LEFT SIDE ON FILLING STORAGE SHELVES. 1 FILING BOX FIXED PEDESTAL + 1 FIXED PEDESTAL WITH 3 EQUAL DRAWERSIN PROVIDED WITH CENTRAL LOCK FOR SECURITY AND HANDLES ARE PROVIDED FOR EASY OF OPENING. OVERALL CONSTRUCTION OF PEDESTAL IS 18 MM ALONG WITH FECA OF DRAWERS. THE SELLER / OEM SHOULD BE NABCB CERTIFIED ISO9001:2015; ISO14001:2015; ISO45001:2018; ISO50001:2018. UL-GREENGUARD GOLD , GRIHA, CII Certified Green Co Gold Certificate, CII Certified GREENPRO, AIOTA, CERTIFIED. THE BIDDER SHOULD ALSO BE A MEMBER OF BIFMA AND ONE OR MORE PRODUCTS OF THE OEM SHOULD BE CERTIFIED AS BIFMA COMPLIANT AND AN OFFICIAL PRODUCT LINK/SCREENSHOT OF THE PRODUCT LISTING'S MUST BE PROVIDED FROM WWW.BIFMA.ORG" IN EACH CASE.	1	NO's
7	Mid back revolving chair	Providing, supplying and placing of High Back Chair with following specifications: SEAT/BACK ASSEMBLY: The seat is made up of 12mm thk. hot pressed plywood measured.The Back is made up of injection moulded glass filled nylon & upholstered with high quality fabric. *HIGH RESILIENCE (HR) POLYURETHANE FOAM: The HR polyurethane seat foam is moulded with density 45+/-2 kg/m³ and hardness 16 ± 2 kgf as per IS:7888 for 25% compression. ARMRESTS : The adjustable armrest is designed with the following features : •Up-Down adjustment •Height adjustable armrest structure which is Powder Coated & fitted with an armrest top. •Fixed Armrest Top is PU moulded over metal insert. LUMBAR SUPPORT ASSEMBLY: The Lumbar support consists of polypropylene pad with moulded polyurethane foam & covered with polyester fabric.The Height of Lumbar pad can be adjusted through two projecting knobs provided on the rear side of the pad. Overall dimension - 710 (W) x 700 (D) x 1170/1270 (H) mm Synchronic mechanism & PNEUMATIC HEIGHT ADJUSTMENT. The pneumatic height adjustment has an adjustment stroke of 10.0 ± 0.3 cm. Pedestal Assembly : the pedestal is injection moulded in black 30% glass filled nylon and fitted with 5 nos. twin wheel castors. The pedestal pitch center dia is 66.1± 0.5 cm. TWIN WHEEL CASTORS: The twin wheel castors are injection moulded in black Nylon. NECKREST : The Neckrest assembly consist of polypropylene pad with moulded polyurethane foam & covered with polyester fabric Neckrest is fixed to Back Assembly through Neckrest connector Neckrest assembly has height adjustment of 4.2 ± 0.5 cm and rotation adjustment of overall 76°+ 2°. The complete neckrest assembly is retro fit to the main chair., etc., all complete as per directions of the Engineer-in-charge.	1	NO's
8	Tools Storage unit / Slotted Angle rack	SUPPLYING AND PLACING IN POSITION OF SLOTTED ANGLE RACK (TYPE - CLSOED FROM TWO SIDE MATERIAL : MILD STEEL SIZE : (L900MM X (D450MM X (H1800MM. COLOUR : GREY & SMOKE GREY / FINISH : EPOXY POLYESTER, WEIGH OF PRODUCT : 46 KG APPROX, CONSTRUCTION : CO2 WELDED . * SUPPLYING AND PLACING OF SLOTTED ANGLE RACK AS PER PHOTOGRAPH. THE RACK SHELF PANEL SHALL BE MADE OF 0.9MM THICK. THE COMPLETE RACK METAL HAING 20 GAUGE. 6 SHELVES INCLUDING TOP & BOTTOM,THESE COMPONENTS SHALL BE MADE OF CRCA 'D' GRADE HIGH YIELD STRENGTH AS PER IS:513 & IS:304 GRADE. ANGLES : 40MM X 40MM X 2MM(THICK. SHELF : 48X15X1MM CRCA SHEET. STEEL COMPONENTS ARE PRE IS:304 GRADE TREATED WITH ANTI RUST TREATMENT AND DULY POWDER COATED MINIMUM 50 MICRONS AS PER APPROVED SHADES	10	NO's
9	Visitor chair - Indoor/outdoor	Supply and place of Visitor chair - Plastic moulded chair with fabric cushion.OUTDOOR/INDOOR DUAL PURPOSE CHAIR Overall dimensions - Width 560mm x Depth 580mm x Height 800mm * High-quality plastic construction for lasting durability. * Ergonomic design with cushioned seat and backrest. * The glossy lacquered finish resists UV rays and rust. * Soft-feel fabric adds a touch of comfort and beauty. * Easy to clean and maintain, Suitable for indoor and outdoor. Chair colour options - Red, Blue, Brown & Metallic Look and Light Beige Cushion.	24	No's
10	Luna Center Table (Wenge)	Providing, assembling and placing of Center table - Width (cm) 100 Depth (cm) 60 Height (cm) 44 Material Primary Material Glass - Tempered Glass Secondary Material Engineered Wood - MDF Product Weight - 21 Kg Thick Glass tabletop enhances the overall aesthetics MDF legs provide excellent support and stability Bottom shelf to hold your books and magazines	2	No's